

noxa

Price list 2023

OFFER VALID FROM 04.10.2023 r.



noxa.pl

Table of Contents

NOXA HEAT

- 3 Heat pump TROPICO (SPLIT, MONO, ALL IN ONE)
- 4 Heat pump COMBO
- 5 Domestic Hot Water Tank VOLCANO
- 5 Hanging/standing buffer tank

NOXA FOR YOU

- 6 Air conditioner HAPPY series
- 7 Air conditioner LUCKY series
- 8 MULTI Series
- 10 Portable air conditioners SMILE & JOY Series
- 11 PROFESSIONAL Series

NOXA AQUA

- 11 Commercial Heat Pumps
- 16 Fan coils

NOXA AIR

- 17 Heat recovery NXCFA series
- 18 Heat recovery NXWRV series
- 18 Heat recovery NXERV series
- 19 Air curtains Blue King Series

OFFER VALID FROM 04.10.2023 r.

Nabilaton Sp. z o.o. reserves the right to change prices.

Prices are in EUR.

The price list is not an offer accordingly to the law.

Units technical specifications as at the day of publication.

The manufacturer reserves the right to make changes in the specifications without prior notification.

The units contain fluorinated greenhouse gases (R134A GWP=1430, R290 GWP=3, R32 GWP=675, R410A=2088).



Heat pump TROPICO - Split Series

Set	Net price [EUR]	Outdoor unit	Indoor unit (hydraulic module)	Capacity [kW]		Heating/cooling capacity coefficient		Power supply [V/Ph/Hz]
				Heating	Cooling	COP	EER	
				A7W35	A35W18	A7W35	A35W18	
TROPICO-SPLIT-4A1HB	2 389	NXHPS-V4W/D2N8-B	NXHB-A60/CD30GN8-B	4.3	4.5	5.2	5.6	220-240/1/50
TROPICO-SPLIT-6A1HB	2 455	NXHPS-V6W/D2N8-B	NXHB-A60/CD30GN8-B	6.2	6.6	5.0	4.9	220-240/1/50
TROPICO-SPLIT-8A1HB	2 556	NXHPS-V8W/D2N8-B	NXHB-A100/CDS90GN8-B	8.3	8.4	5.2	5.1	220-240/1/50
TROPICO-SPLIT-10A1HB	2 735	NXHPS-V10W/D2N8-B	NXHB-A100/CDS90GN8-B	10.0	10.0	5.0	4.8	220-240/1/50
TROPICO-SPLIT-12A1HB	3 127	NXHPS-V12W/D2N8-B	NXHB-A160/CDS90GN8-B	12.1	12.0	5.0	4.0	220-240/1/50
TROPICO-SPLIT-12A3HB	3 294	NXHPS-V12W/D2RN8-B	NXHB-A160/CDS90GN8-B	12.1	12.0	5.0	4.0	380-415/3/50
TROPICO-SPLIT-14A1HB	3 194	NXHPS-V14W/D2N8-B	NXHB-A160/CDS90GN8-B	14.5	13.5	4.7	3.6	220-240/1/50
TROPICO-SPLIT-14A3HB	3 330	NXHPS-V14W/D2RN8-B	NXHB-A160/CDS90GN8-B	14.5	13.5	4.7	3.6	380-415/3/50
TROPICO-SPLIT-16A1HB	3 343	NXHPS-V16W/D2N8-B	NXHB-A160/CDS90GN8-B	16.0	14.9	4.5	3.4	220-240/1/50
TROPICO-SPLIT-16A3HB	3 408	NXHPS-V16W/D2RN8-B	NXHB-A160/CDS90GN8-B	16.0	14.9	4.5	3.4	380-415/3/50

Operating outdoor temperature range: for cooling -5~43°C, for heating -25~35°C, for DHW -25°C~43°C.



Heat pump TROPICO - Mono Series

Model	Net price [EUR]	Capacity [kW]		Heating/cooling capacity coefficient		Power supply [V/Ph/Hz]
		Heating	Cooling	COP	EER	
		A7W35	A35W18	A7W35	A35W18	
NXHPM-V4W/D2N8-BE30	2 199	4.2	4.5	5.1	5.5	220-240/1/50
NXHPM-V6W/D2N8-BE30	2 258	6.4	6.5	5.0	4.8	220-240/1/50
NXHPM-V8W/D2N8-BE30	2 324	8.4	8.3	5.2	5.1	220-240/1/50
NXHPM-V10W/D2N8-BE30	2 448	10.0	9.9	5.0	4.5	220-240/1/50
NXHPM-V12W/D2N8-BE30	3 152	12.1	12.0	5.0	3.9	220-240/1/50
NXHPM-V12W/D2RN8-BER90	3 354	12.1	12.0	5.0	3.9	380-415/3/50
NXHPM-V14W/D2N8-BE30	3 205	14.5	13.5	4.6	3.6	220-240/1/50
NXHPM-V14W/D2RN8-BER90	3 484	14.5	13.5	4.6	3.6	380-415/3/50
NXHPM-V16W/D2N8-BE30	3 228	15.9	14.9	4.5	3.4	220-240/1/50
NXHPM-V16W/D2RN8-BER90	3 610	15.9	14.9	4.5	3.4	380-415/3/50
NXHPM-V18W/D2RN8	On request	18.0	18.5	4.7	4.8	380-415/3/50
NXHPM-V22W/D2RN8	On request	22.0	23.0	4.4	4.6	380-415/3/50
NXHPM-V26W/D2RN8	On request	26.0	27.0	4.1	4.3	380-415/3/50
NXHPM-V30W/D2RN8	On request	30.1	31.0	3.9	4.0	380-415/3/50

Operating outdoor temperature range: for cooling -5~43°C, for heating -25~35°C, for DHW -25°C~43°C.



Heat pump TROPICO - All In One Series

Set	Net price [EUR]	Outdoor unit	Indoor unit (hydraulic module)	Capacity [kW]		Heating/cooling capacity/coefficient		Power supply [V/Ph/Hz]
				Heating	Cooling	COP	EER	
				A7W35	A35W18	A7W35	A35W18	
TROPICO-AIO-4A1/190	3 618	NXHPS-V4W/D2N8-B	NXHBT-A100/190CD30GN8-B	4.3	4.5	5.2	5.6	220-240/1/50
TROPICO-AIO-4A1/240	4 021	NXHPS-V4W/D2N8-B	NXHBT-A100/240CD30GN8-B	4.3	4.5	5.2	5.6	220-240/1/50
TROPICO-AIO-6A1/190	3 679	NXHPS-V6W/D2N8-B	NXHBT-A100/190CD30GN8-B	6.2	6.6	5.0	4.9	220-240/1/50
TROPICO-AIO-6A1/240	4 082	NXHPS-V6W/D2N8-B	NXHBT-A100/240CD30GN8-B	6.2	6.6	5.0	4.9	220-240/1/50
TROPICO-AIO-8A1/190	3 805	NXHPS-V8W/D2N8-B	NXHBT-A100/190CDS90GN8-B	8.3	8.4	5.2	5.1	220-240/1/50
TROPICO-AIO-8A1/240	4 208	NXHPS-V8W/D2N8-B	NXHBT-A100/240CDS90GN8-B	8.3	8.4	5.2	5.1	220-240/1/50
TROPICO-AIO-10A1/190	3 974	NXHPS-V10W/D2N8-B	NXHBT-A100/190CDS90GN8-B	10.0	10.0	5.0	4.8	220-240/1/50
TROPICO-AIO-10A1/240	4 377	NXHPS-V10W/D2N8-B	NXHBT-A100/240CDS90GN8-B	10.0	10.0	5.0	4.8	220-240/1/50
TROPICO-AIO-12A3/240	4 893	NXHPS-V12W/D2RN8-B	NXHBT-A160/240CDS90GN8-B	12.1	12.1	5.0	4.0	380-415/3/50

Operating outdoor temperature range: for cooling -5~43°C, for heating -25~35°C.



Heat pump COMBO series


Model	Net price [EUR]	Heating capacity [kW]	Heaters input power [kW]	Recommended operation range [°C]	Tank volume [l]
NXCMB-190ST-V2	1 372	1.5	3.0	-20~43°C	180
NXCMB-300ST-V2	1 773	3.0	3.0	-20~43°C	280



Domestic hot water tank VOLCANO Plus

Model	Net price [EUR]	Capacity [l]	Dimensions [diameter/high]	Weight [kg]	Coil surface [m ²]
NX-HPDT-200-WCS	817	200	560/1325	48	2.0
NX-HPDT-250-WCS	928	250	560/1505	55	2.5
NX-HPDT-300-WCS	1 058	300	600/1560	62	3.0
NX-HPDT-500-WCS	1 618	500	700/1828	106	4.1

Tank/coil surface material: stainless steel Duplex 2205/SUS 316.
 200, 250, 300l tanks dedicated to work with Noxa heat pumps with a capacity of up to 10kW.
 Volcano Plus tanks can cooperate with gas boilers and fossil fuel boiler



Hanging/Standing buffer tank

Model	Net price [EUR]	Capacity [l]	Dimensions [diameter/high]	Weight [kg]
NX-BT-50-WS	311	50	470/668	19
NX-BT-100-WS	389	100	470/1100	34



Air-conditioners - HAPPY Series

Set	Net price [EUR]	Indoor unit	Outdoor unit	Capacity [kW]	
				Cooling	Heating
SFR-25B-1A	225	NXRA-ID25BFR-1A	NXRA-OD25BFR-1A	2.6	2.8
SFR-35B-1A	240	NXRA-ID35BFR-1A	NXRA-OD35BFR-1A	3.5	3.5
SFR-50B-1A	370	NXRA-ID50BFR-1A	NXRA-OD50BFR-1A	5.3	5.4
SFR-70B-1A	515	NXRA-ID70BFR-1A	NXRA-OD70BFR-1A	7.0	7.0

Available as standard: wireless remote controller.
 Operating outdoor temperature: for cooling -16~48°C, for heating -15~32°C.

Happy Series accesories

Model	Net price [EUR]	Description
M/12100207000136	14	bioHEPA filter
ASK-HAPPY	25	WiFi Module
ZetflowZF-1A	56	Drain pump, max. flow 12 l/h
ZetflowZF-2.0	48	Drain pump, max. flow 24 l/h

NOXA FOR YOU



Air-conditioners - Lucky series

Set	Net price [EUR]	Indoor unit	Outdoor unit	Capacity [kW]	
				Cooling	Heating
SAL-25B-1A	249	NXRM-ID25XWM-1C	NXRM-OD25B-1C	2.6	2.9
SAL-35B-1A	266	NXRM-ID35XWM-1C	NXRM-OD35B-1C	3.5	3.8
SAL-50B-1A	409	NXRM-ID50XWM-1C	NXRM-OD50B-1C	5.3	5.6
SAL-70B-1A	570	NXRM-ID70XWM-1C	NXRM-OD70B-1C	7.0	7.3

Available as standard: wireless controller RG10A4(E)BGEF and WiFi Module OSK-105.
Operating outdoor temperature: for cooling -15~50°C., for heating -15~30°C.



Air-conditioners - Lucky Hot series

Set	Net price [EUR]	Indoor unit	Outdoor unit	Capacity [kW]	
				Cooling	Heating
SAL-25B-1AH	279	NXRM-ID25XWM-1C	NXRM-OD25B-1CH	2.6	2.9
SAL-35B-1AH	296	NXRM-ID35XWM-1C	NXRM-OD35B-1CH	3.5	3.8
SAL-50B-1AH	439	NXRM-ID50XWM-1C	NXRM-OD50B-1CH	5.3	5.6
SAL-70B-1AH	600	NXRM-ID70XWM-1C	NXRM-OD70B-1CH	7.0	7.3

Available as standard: wireless controller RG10A4(E)BGEF and WiFi Module OSK-105.

Lucky Series accesories

Model	Net price [EUR]	Description
OSK-105	25	WiFi Module
WDC-86E/K	60	Wired controller
M/12100207000136	14	bioHEPA filter
ZetflowZF-1A	56	Drain pump, max. flow 12 l/h
ZetflowZF-2.0	48	Drain pump, max. flow 24 l/h

NOXA FOR YOU

Air conditioneres - MULTI Series



Outdoor units

Model	Net price [EUR]	Capacity [kW]		Amount of indoor units	Piping liquid/gas [mm]	Max. Length [m]	Max. Height difference [m]	Recommended operating temperature [°C]	
		Cooling	Heating					Cooling	Heating
NX2OH-14HFN8-Q	457	4.1	4.4	2	2x Ø6.35 / 2x Ø9.52	40	15	-15~50	-15~24
NX2OE-18HFN8-Q	563	5.3	5.6	2	2x Ø6.35 / 2x Ø9.52	40	15	-15~50	-15~24
NX3OG-21HFN8-Q	695	6.2	6.5	3	3x Ø6.35 / 3x Ø9.52	60	15	-15~50	-15~24
NX3OA-27HFN8-Q	718	7.9	8.2	3	3x Ø6.35 / 3x Ø9.52	60	15	-15~50	-15~24
NX4OE-28HFN8-Q	899	8.2	8.8	4	4xØ6,35 / 3xØ9,52+1xØ12,7	80	15	-15~50	-15~24
NX4OB-36HFN8-Q	1 029	10.6	10.8	4	4xØ6,35 / 3xØ9,52+1xØ12,7	80	15	-15~50	-15~24
NX5OE-42HFN8-Q	1 160	12.3	12.3	5	5xØ6,35 / 4xØ9,52+1xØ12,7	80	15	-15~50	-15~24

NEW!

Air conditioneres - MULTI HOT Series



Outdoor units

Model	Net price [EUR]	Capacity [kW]		Amount of indoor units	Piping liquid/gas [mm]	Max. Length [m]	Max. Height difference [m]	Recommended operating temperature [°C]	
		Cooling	Heating					Cooling	Heating
NX2OH-14HFN8-QH	480	4.1	4.4	2	2x Ø6.35 / 2x Ø9.52	40	15	-15~50	-25~24
NX4OE-28HFN8-QH	944	8.2	8.8	4	2x Ø6.35 / 2x Ø9.52	80	15	-15~50	-25~24
NX4OB-36HFN8-QH	1 081	10.6	10.8	4	4xØ6,35 / 3xØ9,52+1xØ12,7	80	15	-15~50	-25~24
NX5OE-42HFN8-QH	1 218	12.3	12.3	5	5xØ6,35 / 4xØ9,52+1xØ12,7	80	15	-15~50	-25~24

NOXA FOR YOU

Lucky Series - indoor units



Model	Net price [EUR]	Capacity [kW]		Piping liquid/gas [mm]	Sound pressure level [dB(A)]
		Cooling	Heating		
NXRM-ID25XWM-1C	73	2.6	2.9	Ø6.35 / Ø9.52	25.0/32.0/38.5
NXRM-ID35XWM-1C	73	3.5	3.8	Ø6.35 / Ø9.52	25.0/34.5/40.5
NXRM-ID50XWM-1C	133	5.3	5.6	Ø6.35 / Ø12.7	26.0/36.0/42.5
NXRM-ID70XWM-1C	144	7.0	7.3	Ø9.52 / Ø15.9	36.0/40.5/45.0

Available as standard: wireless controller RG10A4(E)BGEF and WiFi Module OSK-105.

Ducted units - indoor units



Model	Net price [EUR]	Capacity [kW]		External static pressure [Pa]	Piping liquid/gas [mm]	Sound pressure level [dB(A)]
		Cooling	Heating			
NXLMID-12XDS-1A	277	3.5	3.8	25 (0~60)	Ø6.35 / Ø9.52	23.0/29.0/30.5/34.5
NXLMID-18XDS-1A	321	5.3	5.6	25 (0~100)	Ø6.35 / Ø12.7	26.0/34.0/38.0/41.0

Available as standard: wired remote controller KJR-120C1.

4-way cassette units - indoor units



Komplet	Net price [EUR]	Indoor unit	Panel	Capacity [kW]		Piping liquid/gas [mm]	Sound pressure level [dB(A)]
				Cooling	Heating		
SNXC4C-12N8-A1M	277	NXLMID-12XC4C-1A	T-MBQ4-03E	3.5	3.8	Ø6.35 / Ø9.52	25.5/33.0/36.0/41.0
SNXC4C-18N8-A1M	321	NXLMID-18XC4C-1A	T-MBQ4-03E	5.3	5.6	Ø6.35 / Ø12.7	29.0/35.5/39.5/43.0

Available as standard: wireless controller RG51A(2)/E.

MULTI Series accesories

Model	Net price [EUR]	Description
KJR120C1	34	Wire controller for ducted units
WDC-86E/K	60	Wired controller
WF-60A1	45	WiFi Module for cassette and ducted units



Portable air-conditioners - JOY Series

Model	Net price [EUR]	Capacity [kW]		Air-flow[m ³ /h] (low/medium/high)	Sound pressure level [dB(A)] (low/medium/high)
		Cooling	Heating		
NXP-25CPO1-CA	279	2.6	-	352/366/398	42/44/49
NXP-35CPO1-CA	325	3.5	-	355/370/420	44/46/50
NXP-35CPO1-C	348	3.5	2.9	355/370/420	44/46/50

Available as standard: wireless controller and hot air discharge pipe 1.5 m, ø150.



Portable air-conditioners - SMILE Series

Model	Net price [EUR]	Capacity [kW]		Air-flow[m ³ /h] (low/medium/high)	Sound pressure level [dB(A)] (low/medium/high)
		Cooling	Heating		
NXPAS-025CCO1A	291	2.3	-	330/360/390	35/39/44
NXPA-035CCO1A	325	3.4	-	330/360/391	35/39/45

Available as standard: wireless controller and hot air discharge pipe 1.5 m, ø150.

Portable air conditioners accessories

Model	Net price [EUR]	Description
AIRLOCK	23	400 cm long window sleeve

NOXA PROFESSIONAL



Air-conditioners - Cassette type

Set	Net price [EUR]	Indoor unit	Outdoor unit	Panel
SNXC4C-12N8-A1	684	NXLMID-12XC4C-1A	NXLMOD-12BAU-1A	T-MBQ4-03E
SNXC4C-18N8-A1	794	NXLMID-18XC4C-1A	NXLMOD-18BAU-1A	T-MBQ4-03E

Set	Capacity [kW]		Piping liquid/gas [mm]	Max. length [m]	Max. Height difference [m]	Recommended operating temperature [°C]	
	Cooling	Heating				Cooling	Heating
SNXC4C-12N8-A1	3.5	3.8	Ø6.35 / Ø9.52	25	10	-15~50	-15~24
SNXC4C-18N8-A1	5.3	5.6	Ø6.35 / Ø12.7	30	20	-15~50	-15~24

Available as standards: wireless controller RG51A(2)/E.



Air-conditioners - Ducted

Set	Net price [EUR]	Indoor unit	Outdoor unit	Capacity [kW]	
				Cooling	Heating
SNXDS-12HFN8-A1	684	NXLMID-12XDS-1A	NXLMOD-12BAU-1A	3.5	3.8
SNXDS-18HFN8-A1	794	NXLMID-18XDS-1A	NXLMOD-18BAU-1A	5.3	5.6
SNXDS-48HFN8-A3	1963	NXLMID-48XDS-1A	NXLMOD-48BAU-3A	14.1	16.0
SNXDS-55HFN8-A3	2 029	NXLMID-55XDS-1A	NXLMOD-55BAU-3A	15.2	18.2

Set	External static pressure [Pa]	Piping liquid/gas [mm]	Max. length [m]	Max. Height difference [m]	Recommended operating temperature [°C]	
					Cooling	Heating
SNXDS-12HFN8-A1	25 (0~60)	Ø6.35 / Ø9.52	25	10	-15~50	-15~24
SNXDS-18HFN8-A1	25 (0~100)	Ø6.35 / Ø12.7	30	20	-15~50	-15~24
SNXDS-48HFN8-A3	50 (0~160)	Ø9.52 / Ø15.9	75	30	-15~50	-15~24
SNXDS-55HFN8-A3	50 (0~160)	Ø9.52 / Ø15.9	75	30	-15~50	-15~24

Available as standard: wired remote controller KJR-120C1.

PROFESSIONAL series accessories

Model	Net price [EUR]	Description
KJR120C1	34	Wire controller for ducted units
WDC-86E/K	60	Wired controller
WF-60A1	45	WiFi Module for cassette and ducted units



Fan coils - Cassette standard type

Model	Net price [EUR]	Capacity [kW]	
		Cooling	Heating
4-way Compact (2-pipe system, DC motor)			
NXKA-V600R	367	5.9	8.4
NXKA-V750R	367	6.1	8.3
NXKA-V850R	416	7.5	10.4
NXKA-V950R	416	7.8	10.9
NXKA-V1200R	416	7.9	10.9
NXKA-V1500R	467	11.2	14.9
4-way Compact (4-pipe system, DC motor)			
NXKA-V600FA	401	5.0	7.0
NXKA-V750FA	401	5.2	7.4
NXKA-V850FA	405	5.1	7.7
NXKA-V950FA	414	5.3	7.7
NXKA-V1200FA	465	8.0	11.0
NXKA-V1500FA	469	8.0	11.3

Available as standard: wireless controller.

Cooling conditions: water temperature 7/12°C, air temperature 27°C DB/19°C WB.

Heating conditions: inlet water temperature 50°C, air temperature 20°C DB, same water flow as for cooling.



Fan coils - Cassette compact type

Model	Net price [EUR]	Capacity [kW]	
		Cooling	Heating
4-way Standard (2-pipe system, DC motor)			
NXKD-V300	283	3.0	4.0
NXKD-V400	294	4.0	5.4
NXKD-V500	299	4.2	5.8
4-way Standard (4-pipe system, DC motor)			
NXKD-V300FA	341	2.4	3.9
NXKD-V400FA	343	3.1	4.8
NXKD-V500FA	347	3.1	4.9

Available as standard: wireless controller.

Cooling conditions: water temperature 7/12°C, air temperature 27°C DB/19°C WB.

Heating conditions: inlet water temperature 50°C, air temperature 20°C DB, same water flow as for cooling.

Cassette fan coil accessories

Model	Net price [EUR]	Description
Control		
RM05/BG(T)E-A	25	Wireless controller: timer, backlight
WDC-86E/K	60	Wired controller: heating/cooling mode changeover, temperature display, Follow Me function
CCM15	433	Central controller: reed switch
CCM30	133	Central controller: connection of up to 64 indoor units
Advanced control systems		
LonGW64/E	1 861	LonWorks gateway: up to 64 indoor units
CCM08	1 911	BACnet gateway: up to 64 indoor units
CCM18	2 158	ModBus gateway: up to 64 indoor units
Masking panels		
T-NXBQ4-02C2	112	Panel for Standard version
T-NXBQ4-03B1	59	Panel for Compact version
Valves and actuator		
VG3410JS	25	3-way valve with 3/4" bypass
VG3410ES	25	3-way valve with 1/2" bypass
VA-7088-23	25	On/Off actuator for VG3410xx valves
Drain pans to be placed underneath the valves		
12126200000216	25	Drain pan for NXKA Standard cassette fan coils
12126200000215	13	Drain pan for NXKD Compact cassette fan coils



Fan coils - Ducted

Model	Net price [EUR]	Capacity [kW]	
		Cooling	Heating
3-row heat exchanger (2-pipe system, DC motor)			
NXKT3-V200	275	2.4	3.2
NXKT3-V300	280	3.1	4.5
NXKT3-V400	285	4.0	5.5
NXKT3-V500	285	4.5	6.3
NXKT3-V600	290	5.9	7.8
NXKT3-V800	325	8.0	10.9
NXKT3-V1000	345	9.0	12.6
NXKT3-V1200	375	10.8	14.9
3-row heat exchanger (4-pipe system, AC motor)			
NXKT3-V200F	208	1.4	2.1
NXKT3-V300F	237	2.2	3.0
NXKT3-V400F	241	2.5	3.7
NXKT3-V500F	241	3.0	4.4
NXKT3-V600F	257	4.2	5.7
NXKT3-V800F	378	5.3	6.8
NXKT3-V1000F	407	6.7	8.2
NXKT3-V1200F	423	8.2	10.0

Available as standard: drain pan to be placed underneath the valves.
 Cooling conditions: water temperature 7/12°C, air temperature 27°C DB/19°C WB.
 Heating conditions: inlet water temperature 50°C, air temperature 20°C DB, same water flow as for cooling.

Ducted fan coil accessories

Model	Net price [EUR]	Description
Control		
Colour Touch (FT-CS01)	117	Colour Touch controller: colour screen, heating/cooling adjustment, weekly timer
Simple Touch (T29)	59	Simple Touch controller: temperature display, heating/cooling adjustment, weekly timer, window reed switch
Easy Touch (FT-02)	31	Easy Touch controller: heating/cooling adjustment, wall-mounted
KJR-18B/E-B	25	Wired controller for 2-pipe ducted fan coils
KJR-18B/E-D	36	Wired controller for 4-pipe ducted fan coils
RM05/BG(T)E-A	25	Wireless controller: timer, backlight
CCM15	433	Central controller: data converter
CCM30	133	Central controller: connection up to 64 indoor units
Advanced control systems		
LonGW64/E	1 861	LonWorks gateway: up to 64 indoor units
CCM08	1 911	BACnet gateway: up to 64 indoor units
CCM18	2 158	ModBus gateway: up to 64 indoor units
Valves and actuator		
VG3410JS	25	3-way valve with 3/4" bypass
VG3410ES	25	3-way valve with 1/2" bypass
VA-7088-23	25	On/Off actuator for VG3410xx valves



Ceiling-floor Fan coil

Model	Net price [EUR]	Capacity [kW]	
		Cooling	Heating
3-row, with housing (2-pipe system, DC motor)			
NXKH2-V150-R3	263	1.5	1.6
NXKH2-V250-R3	288	2.4	2.6
NXKH2-V350-R3	318	3.5	3.5
NXKH2-V500-R3	401	4.3	4.3
NXKH2-V700-R3	421	5.6	6.0
NXKH2-V800-R3	438	7.4	8.1
4-row, with housing (4-pipe system, DC motor)			
NXKH2-V150F-R4	276	1.7	1.4
NXKH2-V250F-R4	301	2.7	2.3
NXKH2-V350F-R4	327	3.8	2.9
NXKH2-V500F-R4	418	4.6	3.4
NXKH2-V700F-R4	445	6.1	4.6
NXKH2-V800F-R4	476	7.7	7.5

Available as standard: drain pan to be placed underneath the valves.
 Cooling conditions: water temperature 7/12°C, air temperature 27°C DB/19°C WB.
 Heating conditions: inlet water temperature 50°C, air temperature 20°C DB, same water flow as for cooling.

Ceiling-floor fan coils accessories

Model	Net price [EUR]	Description
Control		
KJRP-75A/BK-E (DC)	36	Wired controller: heating/cooling/auto mode changeover, ± 0,5 °C temperature adjustment, backlit key
KJRP-86A/BMFNKD-E (AC)	59	Wired controller: heating/cooling/auto mode changeover, ± 0,5 °C, temperature adjustment, Modbus protocol
CCM15	433	Central controller: reed switch
CCM30	133	Central controller: connection up to 64 indoor units, automatically reads all connected units
Advanced control systems		
CCM08	1 911	BACnet gateway: up to 64 indoor units
CCM18	2 158	ModBus gateway: up to 64 indoor units
Valves and actuator		
VG3410JS	25	3-way valve with 3/4" bypass
VG3410ES	25	3-way valve with 1/2" bypass
VA-7088-23	25	On/Off actuator for VG3410xx valves



Wall-mounted Fan coils

Model	Net price [EUR]	Capacity [kW]	
		Cooling	Heating
NXKG-V250C	307	2.2	3.0
NXKG-V300C	307	2.6	3.7
NXKG-V400C	318	3.1	4.3
NXKG-V500C	345	4.1	5.7
NXKG-V600C	354	4.5	6.3

Available as standard: drain pan to be placed underneath the valves, Wireless controller RM05/BG(T)E-A.
 Cooling conditions: water temperature 7/12°C, air temperature 27°C DB/19°C WB.
 Heating conditions: inlet water temperature 50°C, air temperature 20°C DB, same water flow as for cooling.

Wall-mounted fan coils accessories

Model	Net price [EUR]	Description
Control		
RM05/BG(T)E-A	25	Wireless controller: timer, backlight
WDC-86E/K	60	Wired controller: heating/cooling mode changeover, temperature display, Follow Me function
CCM15	433	Central controller: reed switch
CCM30	133	Central controller: connection up to 64 indoor units, automatically reads all connected units
Advanced control systems		
LonGW64/E	1 861	LonWorks gateway: up to 64 indoor units
CCM08	1 911	BACnet gateway: up to 64 indoor units
CCM18	2 158	ModBus gateway: up to 64 indoor units
Valves and actuator		
VG3410JS	25	3-way valve with 3/4" bypass
VG3410ES	25	3-way valve with 1/2" bypass
VA-7088-23	25	On/Off actuator for VG3410xx valves

NOXA AQUA



Commercial Heat Pumpst

Model	Net price [EUR]	Capacity [kW]		Czynnik chłodniczy [Typ /Ilość kg]
		Cooling	Heating	
MDVM-V65D2BR8-AS	On request	65	57	R32/9
MDVM-V75D2BR8-AS	On request	75	70	R32/9
MDVM-V110D2BR8-AS	On request	110	100	R32/15,5
MDVM-V140D2BR8-AS	On request	140	130	R32/15,5
MDVM-V65MD2BR8-AS	On request	65.7	56.68	R32/9
MDVM-V75MD2BR8-AS	On request	75.7	69.29	R32/9
MDVM-V110MD2BR8-AS	On request	110.7	99.33	R32/15,5
MDVM-V140MD2BR8-AS	On request	140.9	129.29	R32/15,5

Operating range for outdoor temperature: heating: -25°C ~ 43°C; cooling: -15°C ~ 48°C
 Supply water temperature range: heating: 25°C ~ 65°C; cooling: 0°C ~ 20°C



NXCFA heat recovery Series

Model	Net price [EUR]	Air-flow [m ³ /h] (high speed)	Temperature recovery efficiency [%] (high speed)	Static pressure [Pa] (high speed)	Sound pressure level [dB(A)]
NXCFA-250TV1	1 478	250	85	130	35
NXCFA-350TV1	1 594	350	85	150	37
NXCFA-500TV1	1 721	500	85	160	39

Available as standard: wired controller, G4 filters, WiFi Module.

NXCFA heat recovery accessories

Model	Net price [EUR]	Description
NXCFA_FLT7.2.3	19	High efficiency (absolute) filter
NXCFA_FLT7.5	23	High efficiency (absolute) filter
NXCFA-ST1	64	Touch controller
NXCFA_CO2	100	CO ₂ sensor



Heat recovery - NXWRV Series

Model	Net price [EUR]	Air-flow [m³/h] (high speed)	Temperature recovery efficiency [%] (high speed)	Sound pressure level [dB(A)]
NXWRV-150V2S1	680	150	82	23-36

Available as standard: wireless controller and a set of filters (pre-filter, with active carbon, HEPA filter), WiFi Module (NXWRV-150V2S1).



Heat recovery ventilator - NXERV AC Series

Model	Net price [EUR]	Air-flow [m³/h] (high speed)	Temperature recovery efficiency [%] (high speed)	Enthalpy recovery efficiency [%] (high speed)		Static pressure [Pa] (high speed)
				Cooling	Heating	
NXERV - 400ACV1	601	400	69	57	60	88
NXERV - 600ACV1	682	600	70	59	61	97
NXERV - 800ACV1	937	800	68	55	57	100

Available as standard: wall-mounted controller NXERV_ST2, air supply and exhaust G3 pre-filter.



Heat recovery ventilator - NXERV DC Series

Model	Net price [EUR]	Air-flow [m³/h] (high speed)	Temperature recovery efficiency [%] (high speed)	Enthalpy recovery efficiency [%] (high speed)		Static pressure [Pa] (high speed)
				Cooling	Heating	
NXERV-150V1	583	150	75	63	60	70
NXERV-250V1	607	250	73	65	62	90
NXERV-350V1	676	350	74	65	62	140
NXERV-500V1	823	500	76	67	63	110
NXERV-650V1	989	650	74	65	60	100
NXERV-800V1	1 089	800	76	65	63	140
NXERV-1000V1	1 170	1000	76	62	60	140
NXERV-1300V1	1 293	1300	74	59	58	135
NXERV-1500V1	2 159	1500	76	65	63	95
NXERV-2000V1	2 343	2000	76	62	60	115

Available as standard: wall-mounted controller NXERV_ST2, air supply and exhaust G3 pre-filter and F9 fine filter.

NXERV heat recovery ventilator accessories

Model	Net price [EUR]	Unit model	No. of filters in the unit	Description
H10 class filters				
NXFLT10.1	36	NXERV-150V1	1	High efficiency (absolute) filter
NXFLT10.2	36	NXERV-250V1	1	
NXFLT10.3	72	NXERV-350V1	2	
NXFLT10.4	72	NXERV-500V1	2	
NXFLT10.7	142	NXERV-650V1	2	
NXFLT10.5	164	NXERV-800V1	2	
NXFLT10.6	188	NXERV-1000V1	2	
NXFLT10.6	188	NXERV-1300V1	2	
NXFLT10.7	284	NXERV-1500V1	4	
NXFLT10.5	328	NXERV-2000V1	4	
Control				
NXERV_ST2	71	all NXERV models	-	Wall-mounted touchcontroller with weekly timer - standard accessories
Sensors				
ERV_WIFL_MODULE	30	all models	-	WiFi Module
NXERV_HMD	48	all models	-	Humidity sensor
NXERV_CO ₂	129	all models	-	CO ₂ sensor
Electric pre-heater				
NXENO-160-1.0-1-CBF	322	NXERV-150V1, NXERV-250V1	-	Electric pre-heater with capacity of 1,0 kW
NXENO-160-1.6-1-CBF	322	NXERV-350V1	-	Electric pre-heater with capacity of 1,6 kW
NXENO-200-2.0-1-CBF	335	NXERV-500V1	-	Electric pre-heater with capacity of 2,0 kW
NXENO-250-3.0-1-CBF	377	NXERV-650V1, NXERV-800V1	-	Electric pre-heater with capacity of 3,0 kW
NXENO-250-3.6-2-CBF	433	NXERV-1000V1, NXERV-1300V1	-	Electric pre-heater with capacity of 3,6 kW
NXEN-40x40-6.0-3-CBF	516	NXERV-1500V1, NXERV-2000V1	-	Electric pre-heater with capacity of 6,0 kW



Air curtains - Blue King Series

Model	Net price [EUR]	Power supply [V/Hz]	Input power fan [W]/heater [kW]	Air-flow [m³/h]	Air-flow velocity [m/s]	Max. sound pressure level [dB]	Length [mm]
Cold air-curtain							
NXACC101000AV2	94	220-240/1/50	150/-	1980/1164	11	≤43	1000
NXACC151000AV2	117	220-240/1/50	220/-	2970/1747	11	≤46	1500
NXACC201000AV2	175	220-240/1/50	320/-	3960/2329	11	≤51	2000
Hot air-curtain							
NXACH101045EV1	198	220-240/1/50	180/4,5	1100/647	7-8	≤45	1000
NXACH151055EV1	233	220-240/1/50	220/5,5	1800/1059	7-8	≤47	1500
NXACH203100EV1	291	220-240/1/50	320/10	2400/1412	7-8	≤51	2000

Available as standard: wireless controller.

noxaxa



noxaxa.pl